
SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 752 Ink
COLORS: All colors
MANUFACTURER: Specialty Ink Company, Inc.
ADDRESS: 20 Dunton Avenue
Deer Park, NY 11729
EMERGENCY PHONE: 800-688-4005 - VEOLIA
OTHER CALLS: 631-586-3666
FAX PHONE: 631-586-3666
PREPARED BY: Keith Werwa

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS NO.</u>	<u>% VOL</u>	<u>SARA 313 Reportable</u>	<u>Exposure Limit ACGIH-TLV</u>	<u>Exposure Limit OSHA PEL</u>
Diacetone Alcohol	123-42-2	15-20		50 ppm	50 ppm
Butyl Alcohol	71-36-3	15-20	Yes	20 ppm	100 ppm

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Do not get in eyes or on clothing. Do not breathe vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

ROUTES OF ENTRY: Dermal contact. Eye contact. Inhalation. Ingestion.

POTENTIAL ACUTE HEALTH EFFECTS

EYES: Irritation to eyes

SKIN: May cause slight irritation to sensitive skin

INGESTION: May cause nausea and or vomiting

INHALATION: Avoid prolonged breathing of vapors. May cause irritation to the respiratory system.

SECTION 4: FIRST AID MEASURES

EYES: Affected individual should remove contact lens, if present. In case of contact with eyes, rinse immediately with plenty of water or saline solution. Get medical attention if irritation occurs.

SKIN: Flush excess with soap and water.

INGESTION: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately

INHALATION: If inhaled, remove to fresh air. Get medical attention if symptoms appear. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: 11.1
(% BY VOLUME) LOWER: 2.0

FLASH POINT: 88 F
METHOD USED: Closed cup

AUTOIGNITION TEMPERATURE: 659 F

HMIS HAZARD CLASSIFICATION

HEALTH: 1

FLAMMABILITY: 3

REACTIVITY: 0

PROTECTION: A

EXTINGUISHING MEDIA: Carbon dioxide. Dry chemical. Alcohol Foam. Water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

SECTION 5 NOTES: Avoid heat, sparks and open flame. Slightly flammable to flammable in presence of heat. Use an extinguishing agent suitable for surrounding fires.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Remove sources of ignition. Ventilate.

ENVIRONMENTAL PRECAUTIONS: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

METHODS FOR CLEANING UP:

Small spill and leak: Absorb with an inert material and place in an appropriate waste disposal container.

Large spill and leak: Contain and cover spill with an absorbent material. Collect and dispose in chemical waste drum. Use appropriate containment to avoid environmental contamination. Place spilled material in an appropriate container for disposal.

SECTION 7: HANDLING AND STORAGE

HANDLING: Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Use only with adequate ventilation. Do not breathe vapor or mist. Wash thoroughly after handling.

STORAGE: Keep container tightly closed. Keep container in a cool, well ventilated area.

STORAGE TEMPERATURE: 0-120 F

SHELF LIFE: 9 months from date of manufacture

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

EYE PROTECTION: Safety eyewear complying with an approved standard should be use when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

SKIN PROTECTION: Gloves for cleanliness.

PERSONAL PROTECTION IN CASE OF LARGE SPILL: Splash goggles.

EXPOSURE GUIDELINES: See section 2

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE AND APPEARANCE: Liquid

ODOR: Mild

BOILING POINT: 244 F

MELTING POINT: -127 F

VAPOR PRESSURE (mmHg): 5.5

VAPOR DENSITY (AIR = 1): 4.0

SPECIFIC GRAVITY (H2O = 1): .810

REACTIVITY IN WATER: None

SOLUBILITY IN WATER: Negligible

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Heat, sparks and open flame

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Burning may produce CO and CO2

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID (POLYMERIZATION): None

SECTION 11: TOXICOLOGICAL INFORMATION

DIACETONE ALCOHOL TOXICOLOGICAL INFORMATION: Oral rat LD50 > 2000mg/kg; inhalation rat LC50 greater than near saturated vapour concentration/ 1H, dermal rabbit LD50 > 2000mg/kg

BUTYL ALCOHOL TOXICOLOGICAL INFORMATION: Eyes: No data available; Skin : Acute dermal LD50 (rabbit): 3,400 mg/kg; Inhalation Acute 4 hours LC50 (rat): 8 mg/l; Ingestion Acute oral LD50(rat): 750 mg/kg

Effects of chronic exposure: Skin and eye irritant. Injury to liver and kidneys.

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL TOXICITY

DIACETONE ALCOHOL:

Fish: LC/EC/IC50 > 100 mg/l

Aquatic Invertebrates: LC/EC/IC50 > 1000 mg/l

Aquatic Plants: LC/EC/IC50 > 1000 mg/l

BUTYL ALCOHOL:

Aquatic toxicity

Non-toxic to aquatic life.

LC50 (P. Promelas (fathead minnow)) 96 hours 1,740 mg/l

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. The user of this material has the responsibility to dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14: TRANSPORT INFORMATION

Refer to the following when using the below information and reshipping Inks and Thinners:

FLASH POINT 73 – 149 (HAZARDOUS BY GROUND IN 5 GALLON CONTAINER)

FLASHPOINT UNDER 73 (HAZARDOUS BY GROUND IN QUART OR LARGER CONTAINER)

AND FLASHPOINT 149 OR UNDER (HAZARDOUS BY AIR IN ANY UNIT OF MEASURE)

If size deems shipment hazardous, below markings are required

U.S. DEPARTMENT OF TRANSPORTATION (LAND, D.O.T.)

PROPER SHIPPING NAME: Printing Ink

HAZARD CLASS: 3

ID NUMBER: 1210

PACKING GROUP: III

WATER TRANSPORTATION (WATER, I.M.O.)

PROPER SHIPPING NAME: Combustible Liquid
HAZARD CLASS: 3
ID NUMBER: 1993
PACKING GROUP: III

AIR TRANSPORTATION (AIR, I.C.A.O.)

PROPER SHIPPING NAME: Printing Ink
HAZARD CLASS: 3
ID NUMBER: 1210
PACKING GROUP: III

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA (TOXIC SUBSTANCE CONTROL ACT) LISTED:

Diacetone Alcohol	123-42-2
Butyl Alcohol	71-36-3

311/312 HAZARD CATEGORIES: "Fire Hazard", "Immediate Accute Health Hazard", "Flammable Liquid"

U.S. FEDERAL REGULATIONS: Butyl Alcohol is subject t otreporting requirements of SARA Title III, Section 313 of the Emergency Planning Community Right to Know Act of 1986 and of 40 CFR 372. This product is in compliance with the EPA TSCA inventory.

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: The hazards listed on this MSDS are taken from the MSDS for each of the ingredients in this mixture. In most cases, the maximum form of hazard is represented here. The TLV's represent the conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect . It must be remembered that each individual reacts differently and some may experience discomfort while others do not. This MSDS is presented so that each individual will have the information to deal safely with the use of this product. All material's TSCA listed.

PREPARATION INFORMATION: Prepared by Specialty Ink Company, Inc.

DATE PREPARED: November 3, 2011

SUPERCEDES ALL PREVIOUSLY DATED MSDS

DISCLAIMER: As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim all liability for any use of this material. Information contained heein is given in good faith and is believed to be true and accurate. All statements or suggestions are made without any warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or results to be obtained from the use thereof.